
Footbridge Reconstruction Workshop #2 Town of Boothbay Harbor, ME

July 12, 2018 BAKER DESIGN CONSULTANTS Civit, Manne, & Structural Engineering.


Presentation Outline

- Project Location and Overview
- Footbridge History
- 3. Existing Conditions
- 4. Project Purpose and Need
- Reconstruction Options
 - A. Key design parameters and input received to date
 - B. Present Conceptual Designs
- 6. Next Steps
- 7. Feedback


1. Project Location and Overview



1. Project Location and Overview



1. Project Location and Overview





2. Footbridge History


- 1901 Original bridge constructed by Luther Maddocks at a cost of \$1,500. Bridge originally had a hand-operated swing span to allow large vessels to reach head of harbor.
- Winter 1917-1918 bridge damaged by icing and repaired
- 1928 bridge damaged by icing and repaired
- Originally 1,000-ft long, the bridge was at some point shortened by 300-ft by filling at ends. Parking Lots created at each end (currently Town Lot and Squirrel Island Lot)
- 1978-1979 Complete reconstruction of bridge completed by Mace Carter at a cost of \$135,000.
- **2017** Pile bracing and swing span repair





EXACT DATE this photo was taken is not known, but it is believed to have been 1917, one of the years the harbor froze over. This picture was submitted for use in the Register by Mrs. Ethel Fowler of the Bridge House Studio in Boothbay Harbor.




















- The Footbridge is an important piece of the Town of Boothbay Harbor's Infrastructure
 - Transportation
 - Access across harbor
 - Access to Town dock
 - Access to private property
 - Destination
 - Public access to the harbor for scenic viewing
 - Part of the character of Boothbay Harbor
- Why reconstruct the footbridge?

Existing Structure built in 1978-1979

- Currently over 39 years old
- This represents a significant portion of the expected service life of a timber structure in a coastal environment
- Investments should consider long-term economics and feasibility

2. Swing Span

- USCG classifies the Footbridge as a movable bridge
- Not functional in recent history
- Per USCG, Town is responsible for opening the bridge if need arises
- Operation of movable bridge should be restored or the Town should work with USCG to change the bridge classification


3. Structural Capacity


- Code requirement for pedestrian live load is 90-100 psf
- Superstructure rated at 50 psf live load capacity
- The superstructure must be capable of supporting code-required live loading

4. Flood Hazard Issues

- Structure is very low in relation to tidal and flood elevations
- Top of Deck ranges from 8.2' NAVD88 to 9.5' NAVD88
- Base Flood Elevation (BFE) = 11.0' NAVD88
- Highest Annual Tide (HAT) = **6.4**' NAVD88 (Maine DEP 2017 Predictions)
- These values do not account for Sea Level Rise























4. Flood Hazard Issues

- Structure is at significant risk of damage during flood events
- Opportunities: Elevate, Resist (Wet Floodproof), Combination
- Regulatory Requirements

Town of Boothbay Harbor Flood plain Management Ordinance

§170-92 Development Standards

- **M.** Bridges. New construction or substantial improvement of any bridge in Zones A, AE and VE shall be designed such that:
 - (1) When possible, the lowest horizontal member (excluding the pilings, or columns) is elevated to at least one foot above the base flood elevation; and
 - (2) A registered professional engineer shall certify that:
 - (a) The structural design and methods of construction shall meet the elevation requirements of this section and the floodway standards of § 170-92K; and
 - **(b)** The foundation and superstructure attached thereto are designed to resist flotation, collapse and lateral movement due to the effects of wind and water loads acting simultaneously on all structural components. Water loading values used shall be those associated with the base flood.
- **O.** Wharves, piers and docks. New construction or substantial improvement of wharves, piers, and docks are permitted in Zones A, AE, and VE, in and over water and seaward of the mean high tide, if the following requirements are met:
 - (1)Wharves, piers, and docks shall comply with all applicable local, state, and federal regulations; and
 - **(2)**For commercial wharves, piers, and docks, a registered professional engineer shall develop or review the structural design, specifications, and plans for the construction.

Full compliance with the Floodplain Management Ordinance requires the Top of Deck Elevation to be increased by **4.5'** at the Swing Span.

5. Code Compliance Issues

- ADA (stairs to wharf, deck surface irregularities)
- Handrails (insufficient structural capacity)

6. Utilities

- Water, sewer, electric
- Swing span mechanism subject to flooding





Conclusion:

The most feasible solution is a <u>Replacement</u> of the existing footbridge

5. Reconstruction Options

Design Parameters

- General
 - Structural and Code Requirements
 - Uses and users
 - Navigational Needs
 - Historic Considerations

Geometric

- Structure Location and Horizontal Alignment
- Vertical Alignment/Elevation/Gradients
- Width

Structure Type


- Type and Materials
- Inclusion of a movable span

Features

- Lighting
- Railings
- Utilities
- Aesthetics
- Incorporation with Town dock and other adjacent facilities/improvements
- Site improvements/overlooks/landings













Landings





Existing Bridge



































6. Timeline and Next Steps


- Workshop #2
 - Present preliminary design concepts
 - Gather input on preferred concept and design details
- Prepare Preliminary Design Report
- Permitting and Final Design pending acceptance of Preliminary Design
- Maine DOT funding for a portion of the project is programmed for 2020
- Additional funding pending


7. Feedback


- Some key items to consider:
 - Preferred concept
 - Navigation span requirements
 - Bridge aesthetics and material preferences
 - Overlook and Town Dock design
 - Any other items we should be aware of

Concept Option 1

Concept Option 2







Footbridge Reconstruction Workshop #2

Town of Boothbay Harbor, Maine

July 12, 2018



Questions, contact:

Daniel Bannon, PE, CFM

Baker Design Consultants

7 Spruce Road

Freeport, ME 04032

d.bannon@bakerdesignconsultants.com

207-846-9724



